



PRODUCT DATA SHEET

TROPHY Automotive Engine Oil

20W50 SG/CD

Code:100

TROPHY is suitable for the lubrication of older types of cars, light commercials and diesel engines where API SG petrol rating or CD diesel rating is required.

SPECIFICATIONS

TROPHY meets or exceeds the following specifications.

- API SG/CD
- SAE 20W50
- CCMC G4, D4, PD-2
- US MILITARY MIL-L-465152D

APPLICATIONS

TROPHY is suitable for L.P.G. vehicles and is particularly suited for use in four stroke petrol engines equipped with emission control and PVC systems and will provide protection against wear, sludge formation and acid corrosion.

TROPHY is also suitable for use in diesel engines both naturally aspirated and turbo charged.

TROPHY will assist in controlling oil consumption in worn engines and also protect against oxidation and will maintain its viscosity characteristics over the service life and provide a high level of protection against wear.

TROPHY assists in maintaining engine cleanliness.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	20W50
Specific gravity at 15 C	0.892
Viscosity at 40 C, mm ² /s (cSt)	180
Viscosity at 100 C, mm ² /s (cSt)	18.6
Viscosity index	115
TBN, mgKOH/g	7.5
Sulphated ash, %	0.96

PACKAGE SIZE 1, 4, 5, 20, 60 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary to manufacturing tolerances.