



PRODUCT DATA SHEET

EXTREME

Synthetic Automotive Engine Oil

10W50 SL/CF

Code:200

EXTREME is a fully synthetic, energy conserving motor oil which provides the highest level of protection heat induced oil oxidation, combustion and sludge deposits.

SPECIFICATIONS

EXTREME meets or exceeds the following specifications.

- API SL/CF
- SAE 10W50
- ACEA A3/B3
- JASO VTW
- DAIMLER BENZ DB 229.1
- VW 500.00 / 505.00
- CCMC G5, D4, PD-2
- MIL-L-46152D

APPLICATIONS

EXTREME is suitable for all late model passenger cars especially those fitted with turbo chargers. Ideal for use in L.P.G. fuelled vehicles and diesel engines where API CF performance is stipulated or MIL-L-46152D level of performance is specified.

EXTREME is a high viscosity, low pour point motor oil ensuring quick lubrication to all moving parts during cold weather starts.

EXTREME meets or exceeds the requirements of an SL petrol engine oil. It provides the highest level of protection against wear, sludge formation and acid corrosion thereby extending engine life and maintaining outstanding engine cleanliness.

EXTREME is suitable for air cooled and liquid cooled 4 stroke motorcycle engines and transmissions with wet clutch design. The clutch frictional characteristics are not affected by **EXTREME**.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	10W50
Specific gravity at 15 C	0.878
Viscosity at 40 C, mm ² /s (cSt)	110
Viscosity at 100 C, mm ² /s (cSt)	17.6
Viscosity index	175
TBN, mgKOH/g	8.8
Flash Point C	227

PACKAGE SIZE 5, 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.