



# PRODUCT DATA SHEET

## M1 SPECIAL Semi-Synthetic Automotive Engine Oil

10W40 SN/CF

Code:201

**M1 SPECIAL** is a semi-synthetic oil which provides better protection from piston deposits, less oil thickening and sludge deposits and exceptional anti-wear protection under high speed and high stress.

### SPECIFICATIONS

**M1 SPECIAL** meets or exceeds the following specifications.

- API SN/CF
- ACEA A3/B3/B4
- DAIMLER BENZ DB 229.1
- SAE 10W40
- VW 500.00 / 505.00

### APPLICATIONS

**M1 SPECIAL** is suitable for all late model petrol engine vehicles including those fitted with turbo chargers. Ideal for use in L.P.G fuelled vehicles and diesel engines where API CF performance or better is stipulated.

**M1 SPECIAL** meets or exceeds the requirements of an SN/CF engine oil. It provides a high level of protection against wear, sludge formation and acid corrosion.

**M1 SPECIAL** assists in maintaining engine cleanliness and additionally assists in energy conservation and fuel economy.

### TYPICAL MAIN CHARACTERISTICS

| CHARACTERISTICS                            | 10W40 |
|--|-------|
| Specific gravity at 15 c                   | 0.88  |
| Viscosity at 40c, mm <sup>2</sup> /s (cSt) | 100   |
| Viscosity 100c, mm <sup>2</sup> /s (cSt)   | 14    |
| Viscosity index                            | 142   |
| TBN, mgKOH/g                               | 9.1   |
| Flash Point C                              | 227   |

**PACKAGE SIZE** 1, 6.5, 20, 60 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.