

EUROMAX 504
Synthetic Automotive Engine Oil5W30
Code:205

EUROMAX 504 is an advanced fully synthetic, low ash multi functional oil formulated using the highest quality synthetic base oils and ultra high performance additives to deliver optimum performance for VW and AUDI diesel and petrol passenger vehicles.

SPECIFICATIONS

EUROMAX 504 meets or exceeds the following specifications.

- VW 504.00/ 507.00
- ACEA C3-10 (2010)
- SAE 5W30
- BMW Longlife LL04
- MB- Approval 229.51
- Porsche C30

APPLICATIONS

EUROMAX 504 meets Euro IV emission standards and is suitable for low emission passenger cars and light duty vehicle engines fitted with Catalytic Converters and Diesel Particulate Filter (D.P.F.) technology.

EUROMAX 504 is engineered to provide excellent deposit control to enhance engine cleanliness and enable long engine life with a high viscosity index and low pour point allows quick lubrication to all moving parts during cold weather starts.

EUROMAX 504 will provide exceptional anti-wear protection due to its extra film strength and has been developed to enhance fuel consumption and reduce emissions.

EUROMAX 504 is suitable for late model Volkswagen and Audi diesel and petrol passenger cars with or without turbo chargers.

TYPICAL MAIN CHARACTERISTICS**CHARACTERISTICS**

Appearance	Clear Amber Liquid
Specific gravity at 15 C	0.85 Typical
Viscosity at 40 C, mm ² /s (cSt)	80 Typical
Viscosity at 100 C, mm ² /s (cSt)	11.0 Typical
Viscosity index	170 Typical
Pour point C	-36 Typical
Flash Point C	220 Typical
Sulphated Ash maximum %	0.80
Phosphorous maximum %	0.09
TBN, mgKOH/g	8 Typical

PACKAGE SIZE 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.