



PRODUCT DATA SHEET

Multi Vehicle CVT Belt and Chain types

Code:214

MULTI VEHICLE CVT is a high performance fully synthetic transmission fluid for both push-belt and chain type Continuously Variable Transmissions.

SPECIFICATIONS

MULTI VEHICLE CVT is suitable for use for the following specifications.

- AUDI (TL 52180; G 052 180)
- BMW/MINI (EZL 799)
- DODGE/JEEP (NS-2/CVTF+4)
- FORD MERCON C
- FORD (CVT 23/CVT 30)
- GM/Saturn (DEX-CVT)
- HONDA HMMF
- HYUNDAI/KIA SP-III
- HYUNDAI GENUINE CVT FLUID
- MERCEDES BENZ (236.20)
- MITSUBISHI (CVTF-J1/SP-III)
- NISSAN (NS-2)
- SUBARU (NS-2)
- SUBARU (Lineartronic CVTF)
- SUZUKI (TC/NS-2)
- SUZUKI (CVT Green 1)
- TOYOTA TC
- VW (TL 52180, G 052 180, G 052 516)

APPLICATIONS

MULTI VEHICLE CVT is a fully synthetic transmission fluid for both push-belt and chain type Continuously Variable Transmissions suitable for use in a wide range of American, European and Asian vehicles.

MULTI VEHICLE CVT has optimal steel-to steel friction profile which delivers high torque capacity as well as anti-shudder performance.

MULTI VEHICLE CVT offers excellent film strength for enhanced wear protection at all metal contact points.

MULTI VEHICLE CVT has improved oxidation stability and excellent low temperature properties.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS

Specific gravity at 25 C	0.849
Viscosity at 40 C, mm ² /s (cSt)	34
Viscosity at 100 C, mm ² /s (cSt)	7.14
Viscosity Index	181
Pour Point deg c	<-30

PACKAGE SIZE

1, 5, 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.