



PRODUCT DATA SHEET

TRANSGEAR 75W80 Synthetic Gear Oil

GL5

Code:215

TRANSGEAR 75W80 is a multi grade lubricant manufactured from synthetic base oil with extreme pressure additives to impart friction reducing and energy conserving properties.

SPECIFICATIONS

TRANSGEAR 75W80 meets or exceeds the following specifications.

- API GL5, MT-1
- SAE 75W80
- SAE J2360
- MACK GO-J
- FORD ESZ M2C-190A, MC20119 A, MC2-104
- GENERAL MOTORS HN-1561, HN-2040
- MILITARY SPECIFICATIONS MIL-PRF-2105E

APPLICATIONS

TRANSGEAR 75W80 should be used in differentials using hypoid and spiral bevel gears as well as manual transmissions.

TRANSGEAR 75W80 offers energy conservation, improved transmission life, easy gear shifting and less maintenance these are the main benefits associated with this product.

TRANSGEAR 75W80 will provide maximum protection to gearboxes and differentials used in modern trucks and four wheel drives towing caravans and boats.

TRANSGEAR 75W80 is designed to give maximum protection to gearboxes and differentials under the most arduous operating conditions where heat and load are major factors.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	75W80
Specific gravity at 15 c	0.87
Viscosity at 40c, mm ² /s (cSt)	54
Viscosity 100c, mm ² /s (cSt)	9.1
Viscosity index	150
Flash Point C	213

PACKAGE SIZE 5, 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.