



PRODUCT DATA SHEET

ENDURO 5W40

FullySynthetic 4 Stroke Motorcycle Oil

API SM
Code:220

ENDURO 5W40 is a fully synthetic 4 stroke motorcycle oil for high performance and competition motorcycles. It has outstanding clutch friction control, superior wear protection for engine and gear as well as better fuel economy and increased power in competitive environments.

SPECIFICATIONS

ENDURO 5W40 meets or exceeds the following specifications.

- API SM
- SAE 5W40
- JASO MA/MA2

APPLICATIONS

ENDURO 5W40 has excellent film strength and lubricity to provide maximum protection against viscosity breakdown, thereby delivering ultimate performance in all modern motorcycles.

ENDURO 5W40 provides superior wear and rust protection to engine and gears for high revving motorcycle engines.

ENDURO 5W40 has excellent detergency and thermal stability which reduce oil thickening and sludge deposits for improved engine cleanliness.

ENDURO 5W40 has outstanding wet clutch control friction as well as superior oil consumption control.

ENDURO 5W40 is the right choice for premium performance of the latest technology motorcycles, including all high performance multi-cylinder, multi-valve, V-Twin, air or water-cooled and those fitted with turbochargers.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS

Specific gravity at 15 c	0.85
Viscosity at 40c, mm ² /s (cSt)	80 Typical
Viscosity 100c, mm ² /s (cSt)	14 Typical
Viscosity Index	165
Flash Point C	> 200

PACKAGE SIZE 1 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.