



# PRODUCT DATA SHEET

## HYDRAULIC JACK OIL Industrial Lubricant

ISO 32  
Code:299

**HYDRAULIC JACK OIL** is premium zinc based anti wear oil formulated from high quality mineral base oils.

### SPECIFICATIONS

**HYDRAULIC JACK OIL** meets or exceeds the following specifications.

- ISO 32
- DENISON HF-0 and HF-2
- VICKERS 35VQ25

### APPLICATIONS

**HYDRAULIC JACK OIL** contains anti rust, antioxidant and anti foam additives.

**HYDRAULIC JACK OIL** is suitable for use in vane pumps, vacuum pumps, hydraulic hoists and jacks where ISO 32 grade oil is called for.

**HYDRAULIC JACK OIL** is a non corrosive hydraulic fluid and offers premium base oils for thermal oxidation stability, rust and corrosion protection, provides good water separation, excellent wear protection, reduces sludge formation, compatible with other hydraulic oils and compatible with rubber and seals.

### TYPICAL MAIN CHARACTERISTICS

#### CHARACTERISTICS

Specific gravity at 15 C	0.87	FZG Stages Passed	12
Viscosity at 40 C, mm <sup>2</sup> /s (cSt)	33	Rust test, ASD66	Pass
Viscosity at 100 C, mm <sup>2</sup> /s (cSt)	5.5	Foam, ASTM D-892	50/0
Viscosity index	102		
Pour point C	-18		
Flash Point C	235		

**PACKAGE SIZE** 1 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.