



PRODUCT DATA SHEET

SLIDEWAY 32 Industrial Lubricant

ISO 32
Code: 348

SLIDEWAY 32 is a mineral base lubricant formulated with selected extreme pressure additives and special additives for tackiness and adhesiveness.

SPECIFICATIONS

SLIDEWAY 32 meets or exceeds the following specifications.

- ISO 32

APPLICATIONS

SLIDEWAY 32 protects saw blades and guides from abrasive wear and can be applied manually or in automatic lubrication systems.

SLIDEWAY 32 is a tacky extreme pressure and anti-wear lubricant with excellent cling characteristics that resists throw off, water wash off and corrosion under high and low speeds.

SLIDEWAY 32 will assist in increasing equipment life.

SLIDEWAY 32 is ideal for lubricating manufacturing machinery under high loads and pressures such as in lathes, milling machines and other equipment with slides and carriage ways.

SLIDEWAY 32 will adhere to the working surfaces under high load and temperature and resist wash out from water soluble cutting fluids.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	ISO 32
Viscosity @ 40 C cSt	32 Typical
Viscosity @ 100 C cSt	6 Typical
Viscosity Index	105 Typical
Flashpoint	203 Typical
Density	0.86

PACKAGE SIZE 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.