



PRODUCT DATA SHEET

INDUSTRIAL GEAR #68 Industrial Lubricant

ISO 68
Code:357

INDUSTRIAL GEAR #68 is a premium quality industrial lubricant containing lead free extreme pressure agents and has been developed to combine high load carrying capacity with good anti-friction characteristics.

SPECIFICATIONS

INDUSTRIAL GEAR #68 meets or exceeds the following specifications.

- ISO 68
- U.S. Steel 224
- AGMA 250.04
- DIN 51517, Part 3

APPLICATIONS

INDUSTRIAL GEAR #68 may be used in all types of industrial enclosed gear assemblies requiring an ISO 68 lubricant. It may also be used as a bearing oil for highly loaded plain bearings.

INDUSTRIAL GEAR #68 will provide excellent high film strength for superior wear protection, high corrosion protection and excellent water demulsibility.

INDUSTRIAL GEAR #68 is particularly suited for steel or bronze industrial worm gears.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	ISO 68
Viscosity at 40 C, (cSt)	68
Viscosity at 100 C,(cSt)	8.7
Viscosity Index	114

PACKAGE SIZE 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.