



PRODUCT DATA SHEET

OIL BOOST TREATMENT Stop It Additives

Code:702

OIL BOOST TREATMENT is a heavy duty oil fortifier that will quieten noisy engines, gears and differentials allowing them to run smoother and burn less oil.

SPECIFICATIONS

OIL BOOST TREATMENT meets or exceeds the following specifications.

. N/A

APPLICATIONS

OIL BOOST TREATMENT is for use in engines that are experiencing wear problems such as piston ring or bearing wear and will boost or restore the viscosity of motor oil that has been reduced through shearing caused by high temperature excursions or excessive periods of high load use.

OIL BOOST TREATMENT is equally suitable for use in gear boxes and differentials. When added it will allow for smoother operation and longer gear box and lubricant life.

OIL BOOST TREATMENT contains a viscosity conditioning agent that assists the lubricant to resist thinning as temperature and loads increase and will improve the performance of most engines while reducing emissions such as smoke and unburnt hydrocarbons

OIL BOOST TREATMENT can be added to both mineral and synthetic oil with no adverse effects.

OIL BOOST TREATMENT should be added to a hot engine and allowed to idle for 2 minutes to thoroughly circulate throughout the engine.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS

Specific Gravity	0.88 typical
Viscosity @ 40 C cSt	1300 typical
Flash Point deg C	Greater than 200

PACKAGE SIZE 350 Mil

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.