



# PRODUCT DATA SHEET

## ENVIROMAX

5W30 ACEA C4

Code:202

**ENVIROMAX** is a top tier fully synthetic engine oil using the latest low SAPs additive technology coupled with highly refined basestocks to deliver enhanced fuel efficiency and optimal protection of the engine plus emission control systems in vehicles where ACEA C4 engine oil is required.

### SPECIFICATIONS

**ENVIROMAX** meets or exceeds the following specifications.

- SAE 5W30
- ACEA C4-12
- MB 229.51
- MB 226.51
- Renault RN 0720

### APPLICATIONS

**ENVIROMAX** is designed for use in modern multi-valve, multi-cam, naturally aspirated and turbocharged diesel and petrol engines including those with or without Diesel Particulate Filters (DPFs).

**ENVIROMAX** has low SAPS (sulphated ash, phosphorus and sulphur) which keeps advanced emission control systems like DPFs and Three Way Catalysts (TCW) in optimal conditions.

**ENVIROMAX** gives maximum wear protection while offering improved fuel economy. Its high viscosity index provides excellent cold start performance, longer drain intervals as well as superior deposit control to maintain engine cleanliness.

**ENVIROMAX** meets the requirements of the European ACEA C4-12 specification. It is approved for use in vehicles designed for Euro 4 & Euro 5 engines that require oils meeting ACEA C4 and Renault RN 0720 specifications, such as selected Renault, Nissan, Jaguar, Land Rover & Suzuki models.

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	5W30
Specific gravity at 15 C	0.84
Viscosity at 40 C, mm <sup>2</sup> /s (cSt)	55 Typical
Viscosity at 100 C, mm <sup>2</sup> /s (cSt)	10.9 Typical
Viscosity index	195 Typical
Flash Point C	220

**PACKAGE SIZE** 6.5 Litre, 20 Litre, 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.