



# PRODUCT DATA SHEET

## RED & TACKY Grease

NLGI 2  
Code:620

**RED & TACKY GREASE** is a lithium complex based grease possessing superior rust inhibition and extreme pressure lubrication characteristics with a smooth and tacky texture suitable for agricultural, earthmoving and industrial applications.

### SPECIFICATIONS

**RED & TACKY GREASE** meets or exceeds the following specifications.

- NLGI 2

### APPLICATIONS

**RED & TACKY GREASE** resists squeeze out from surfaces requiring lubrication under heavy load conditions and has been specially formulated to include a shear stable tackiness agent which imparts extra tenacity for stay put lubrication due to the added adhesive characteristics.

**RED & TACKY GREASE** has a high shear stability which ensures long service life particularly in sealed anti-friction bearings. The excellent resistance to mechanical shear combined with high film strength, maintains grease consistency for extended lubrication service.

**RED & TACKY GREASE** will adhere to and protect the working surfaces from scuffing under unusually high load and shock load conditions thereby increasing equipment life.

**RED & TACKY GREASE** is recommended for ball, roller, sliding surfaces and open gears operating under all service conditions including high and low temperature applications.

### TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	NLGI 2		
Penetration @ 25 Deg C Worked 60 strokes	280	Mineral Oil Viscosity @ 40 C cSt	314
Dropping Point deg C	285	Mineral Oil Viscosity @ 100 C cSt	19.2
Appearance	Red & tacky	Rust Prevention	No Rust
		Timken OK Load, kg	28

**PACKAGE SIZE** 450 Gm, 2.5, 20 & 180 Kg

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.